

A close-up photograph of laboratory equipment. In the foreground, a black cylindrical component with a white knurled top is labeled '1' and 'ortoalresa Ns 220759/05'. To its right, several stainless steel tubes are arranged diagonally, each engraved with 'ortoalresa Ns 220607/02'. In the background, a black tray holds several red caps. A semi-transparent dark grey box in the upper right contains the company logo and tagline.

**orto
alresa**
About centrifugation

Special applications | DIGTOR 22 COL



DIGTOR 22 COL



Essential tool for fat processing, where the highest concentration of stem cells can be found, for liposculpture techniques and reparative surgery.

Features

- Available rotors for tubes (check Digtor 22 accessories, pag. 72-73)

TFT color touch screen, visible from more than 3 m.:

- Shows RPM and RCF, time, acceleration/deceleration values (PCBS) and unbalance location system (ULS).
- Speed programming in 10 RPM/ 10 xg steps
- Real RCF values on screen based on accessories configuration.
- Count up/down from “0” or at “set RPM/RCF” for reproducible tests.
- Timer from 1 sec to 99 hours programmable in 1 sec. steps and hold position.
- PCBS: Progressive controlled acceleration and braking system up to 175 selectable ramps that prevents sample homogenization after separation.
- ULS: Unbalance location system indicating on the screen the number of the bucket which produces the unbalance switch off.
- Start delay: To program the time at which the cycle is to begin.
- Linked program: Permits the linking of up to 8 consecutive programmes without the need of user intervention.
- 100 programmable memories, with protection under password.
- Several acoustic and visual messages showing the situation of the device to the user.

Easy to use

- Microprocessor controlled. Connectivity.
- Induction motor maintenance free (brushless).
- Rotors and adapters list in memory.
- Noise level: below 60 dB.
- Start, stop, open lid and short spin with adjustable speed buttons.
- Possibility to block or modify the speed during the cycle.
- Automatic open lid, programmable.
- Last values remain in memory.
- Automatic rotor recognition. Over-speed protection.

3 YEAR WARRANTY



Max. Capacity
4 x 60 ml



Max. Speed
1.801 xg / 3.000 RPM



Screen Type
TFT



Version
Ventilated



EU Directives: 2011/65/EU, 2012/19/EU, 2014/30/EU, 2014/35/EU.
Standards: EN 61010-1, EN 61010-2-020, EN 61010-2-101, EN 61326-2-6, EN 61326-1.

Safety

- Lid provided with security systems:
 - Automatic lid lock system, motorized with double lock.
 - Emergency lid-lock release.
 - Locking and protection against opening along the run.
 - Lid dropping protection.
 - Port in the lid for calibration and operation checking.
- Unbalance detection and switch off.
- Protection safety ring between the centrifugation chamber and the housing.
- Chamber of centrifugation in stainless steel (easy cleaning).
- Rotors and adapters autoclavable, easy to install by the user.
- Forced ventilation to reduce temperature increasing.
- Automatic disconnection for energy saving up to 8 h., with deactivation option.

Versions

	Dimensions (mm) (w x d x h)			Net Weight (Kg)	Voltage (V)	Frequency (Hz)	Consumption (W)
CE 204	530	640	400	73	220-230	50-60	460
CE 205	530	640	400	73	110-120	50-60	460

Accessories

RT 302



ROTOR		SWING OUT
Max. capacity		4x60 ml
RPM Max.		3.000
Radius (mm)		179
RCF Max. (xg)		1.801

SAMPLE VOLUME	Dim (mm) approx.	ADAPTERS	
		Tubes	Ref.
Syringes 60 ml. / 10 ml.	31x165 / 16x118	4 / 16	- / RE 438



orto
alresa
About centrifugation

Álvarez Redondo S.A.



Los frailes, 121
Pol. Ind. Los Frailes
28814 Daganzo | Madrid

www.ortoalresa.com



(+34) 91 884 40 16



info@ortoalresa.com to ask for information



sat@ortoalresa.com to contact our technical service

sales@ortoalresa.com to contact our comercial department

marketing@ortoalresa.com to contact our marketing department