

A close-up photograph of Ortoalresa centrifuge components. In the foreground, a black plastic rotor is shown with a white cap and a label that reads '1' and 'ortoalresa Ns 220759/05'. To the right, several stainless steel tubes are arranged in a row, each with a label that reads 'ortoalresa Ns 220607/02'. In the background, a black rotor is visible with several red tubes inserted into it. The image is set against a light, blurred background.

orto alresa

About centrifugation

General applications | MINICEN

MINICEN



Your personal centrifuge for the most demanding laboratory. Compact, quick, reliable and with precise control of operating parameters. Indispensable in separation processes for microvolumes, in which the relative centrifugal force must be high. The Minicen centrifuge includes a rotor for twelve 1.5-2 ml. tubes, able to reach 15,000 RPM and up to 15.596 xg. Also supplied with reducers for 0.5-0.6 ml. and 0.2-0.4 ml. tubes, thus covering needs as regards an equipment for all types of microtubes.

The smallest in the family, offering the performance of biggest ones.

Features

- Small footprint: 5 kg. of weight.

LCD screen:

- Shows RPM/ RCF, time, rotor spinning and lid status.
- Speed programming in 100 RPM/100 xg steps.
- Timer from 30 sec. to 999 min. programmable in 1 sec. steps or hold position.
- Timer with countdown at set time.
- Several acoustic and visual messages showing the equipment status to the user.

Easy to use

- Microprocessor controlled.
- PC connection by USB.
- Induction motor maintenance free (brushless).
- Noise level: below 60 dB.
- Start, short spin, stop, open lid, speed, time and RPM/RCF switch buttons.
- Possibility to modify the speed during the cycle.
- Automatic lid opening.
- Last values remain in memory.

Safety

- Lid provided with security systems:
 - Automatic lid lock system, motorized.
 - Emergency lid-lock release.
 - Locking and protection against opening along the run.
 - Lid dropping protection.
 - Port in the lid for calibration and operation checking.
- Unbalance detection and switch off.
- Rotors can be removed with the lid closed. Hermetic lids.
- Rotors and adapters autoclavable, easy to install by the user.
- Ventilation system to reduce temperature increasing.



Max. Capacity
12 x 1,5 - 2 ml



Max. Speed
15.596 xg /15.000 RPM



Screen Type
LCD



Version
Ventilated



EU Directives: 2011/65/EU, 2012/19/EU, 2014/30/EU, 2014/35/EU, 98/79/EC.

Standards: EN 61010-1, EN 61010-2-101, EN 61010-2-020, EN 61326-2-6, EN 61326-1.

Versions



	Dimensions (mm) (w x d x h)				Net Weight (Kg)	Voltage (V)	Frequency (Hz)	Consumption (W)
CE 182	230	270	130		5	230-110	50-60	180

This code includes the next configuration:

Centrifuge Minicen + angle fixed rotor RT 255 with capacity for **12 x 1,5-2 ml.** and adapters for **12 x 0,5-0,6 ml. (RE 509)** and **12 x 0,2-0,4 ml. (RE 510)**.

In the next chart you can find a range of accessories (rotors and adapters) that will increase the versatility of this configuration.

Accessories

	INCLUDED		OPTIONAL	
	RT 255		RT 263	
				
ROTOR	ANGLE FIXED 30 °		ANGLE FIXED 45 °	
Max. capacity	12 x 1,5-2 ml.		16 x 0,2 ml.	
RPM Max.	15.000		15.000	
Radius (mm)	62		52	
RCF Max. (xg)	15.596		13.080	
	ADAPTERS		ADAPTERS	
SAMPLE VOLUME	Tubes	Ref.	Tubes	Ref.
Microtubes 1,5-2 ml.	12	-	-	-
Microtubes 0,5-0,6 ml.	12	RE 509	-	-
Microtubes 0,2-0,4 ml.	12	RE 510	16	-




orto
alresa
About centrifugation

Álvarez Redondo S.A. 

Los frailes, 121
Pol. Ind. Los Frailes
28814 Daganzo | Madrid

www.ortoalresa.com 

(+34) 91 884 40 16 

info@ortoalresa.com to ask for information 
sat@ortoalresa.com to contact our technical service
sales@ortoalresa.com to contact our comercial department
marketing@ortoalresa.com to contact our marketing department